



Technical Data Sheet
INNOLIFT

		40" wide pallet	48" wide pallet
		ERT1000.1500.40	ERT1000.1500.48
Power		Battery	Battery
Capacity	kg (lbs)	1000 (2200 lbs)	1000 (2200 lbs)
Load centre	mm (inch)	600 (23,6")	600 (23,6")
Lifting height	mm h3 (inch)	1500 (59,1")	1500 (59,1")
Loading height	mm h2 (inch)	1300 (51,1")	1300 (51,1")
Own weight	kg (lbs)	420 (924)	430 (946)
Overall lowered height	mm H (inch)	1995 (78,54")	1995 (78,54")
Overall extended height	mm h4 (inch)	3315 (130,51")	3315 (130,51")
Wheel material		Rubber	Rubber
Wheel dimensions, front	mm (inch)	200 x 80 (7,9"x3,1")	200 x 80 (7,9"x3,1")
Wheel dimensions, rear	mm (inch)	200 x 80 (7,9" x 3,1")	200 x 80 (7,9" x 3,1")
Total length	mm L (inch)	1700 (66,92")	1700 (66,92")
Length without forks	mm l3 (inch)	550 (21,65")	550 (21,65")
Width between support legs	mm b4 (inch)	1280 (50,39")	1480 (58,26")
Chassis width	mm B (inch)	1550 (61,02")	1750 (68,89")
Support legs width	mm b3 (inch)	1530 (60,23")	1730 (68,11")
Wheel base	mm y (inch)	1150 (45,28")	1150 (43,31")
Fork dimensions	mm (inch)	175 x 60 (6,89" x 2,36")	175 x 60 (6,89" x 2,36")
Fork length	mm l2 (inch)	1160 (45,67")	1160 (45,67")
Fork width	mm b2 (inch)	540 (21,26")	540 (21,26")
Ground clearance	mm ml (inch)	80 (3,15")	80 (3,15")
Working aisle AST3	mm (inch)	2120 (83,46")	2150 (84,65")
Turning radius	mm Wa (inch)	1420 (55,91")	1450 (57,09")
Parking brake		Electric	Electric
Extra motor for midwheels	W	16	16
Driving motor	kW	0,65	0,65
Lifting motor	kW	0,8	0,8
Battery capacity (AGM)	V / Ah	24 / 36	24 / 36
Charger	V / A	24 / 8	24 / 8

Frendix Oy

Vierikatu 11, 04430 Järvenpää

Finland

© Frendix Oy 2024

Frendix Oy keeps the right for changes